

How to Monitor Apache Cassandra Databases in Nagios XI

Purpose

This document describes how to configure Nagios XI to monitor Apache Cassandra distributed database implementations to ensure that data, as well as the hardware housing it, is operating properly.

NOTE: If you are using Nagios XI 2024, please refer to the [updated doc](#).

What is Apache Cassandra?

Apache Cassandra is an open-source distributed database management system designed to handle large amounts of data across many commodity servers, providing high availability with no single point of failure. Cassandra offers robust support for clusters spanning multiple data centers, with asynchronous master-less replication allowing low latency operations for all clients.

Prerequisite

The monitoring plugin used in this documentation will be executed on the Cassandra server. This means that the NRPE agent will need to be installed on your Cassandra server(s). This documentation assumes that you have installed NRPE as per the following documentation:

[Installing The XI Linux Agent](#)

Editing Files

In the steps of this documentation, you will be required to edit files. This documentation will use the vi text editor. When using the vi editor:

- To make changes press `i` on the keyboard first to enter insert mode
- Press **Esc** to exit insert mode
- When you have finished, save the changes in vi by typing `:wq` and press **Enter**

How to Monitor Apache Cassandra Databases in Nagios XI

Cassandra Monitoring Plugin

This document uses the plugin **Check Cassandra Status and Heap Memory**.

Memory Heap and Other Metrics Retrievable Through JMX:

- <https://exchange.nagios.org/directory/Plugins/Java-Applications-and-Servers/Check-Cassandra-statusand-heap-memory-utilization/details>
- The plugin checks to see that the node is UP, if it is DOWN it will return a CRITICAL status
- The plugin checks the memory heap utilization, a WARNING status at 85% and CRITICAL at 95%

This plugin requires the nodetool utility, which is usually installed on your Cassandra server. To make sure it exists, execute the following command on your Cassandra server:

```
nodetool status
```

You should receive output like the following:

```
Datacenter: dc1
=====
Status=Up/Down
|/ State=Normal/Leaving/Joining/Moving
   Address          Load           Tokens      Owns (effective)  Host ID                               Rack
UN  10.25.7.31        269.32 KB      256         64.9%             5da540c1-d97f-43b9-aaf5-2a823e009eae rack1
UN  10.25.7.33        264.23 KB      256         71.5%             0fef2f3f-aef2-4b93-80ae-60fd6c30ca66 rack1
UN  10.25.7.32        268.69 KB      256         63.6%             43de786f-dfe8-4c6e-8239-6b2ef111a755 rack1
```

Download The Plugin and Test

The first step is to download and test the plugin. Establish a terminal session to your Cassandra server and execute the following commands:

```
cd /usr/local/nagios/libexec
```

The next command is all one line, it's too long for the document so it wraps onto two lines. It's important that the "double quotes" are used and the -O is a capital "oh":

```
wget "https://exchange.nagios.org/components/com_mtree/attachment.php?link_id=3819&cf_id=24" -O cassandra.pl
```

How to Monitor Apache Cassandra Databases in Nagios XI

Now execute these commands to correctly set permissions:

```
chmod +x cassandra.pl
chown nagios:nagios cassandra.pl
```

Now test that the plugin works, to do so execute the following command:

```
./cassandra.pl
```

You should see output similar to:

```
CASSANDRA OK - | heap_mem=8.01
```

If you receive output similar to the following:

```
CASSANDRA CRITICAL - cannot run /usr/share/cassandra/bin/nodetool;
```

It just means the plugin is pointing to the wrong location for the nodetool program. To fix the problem, execute this command to locate nodetool:

```
find / -name nodetool
```

Which should output something like:

```
/usr/bin/nodetool
```

You will need to edit the `cassandra.pl` file and change this line (line 53):

```
my $nodetool_path = '/usr/share/cassandra/bin/nodetool';
```

In this example, the line would be changed to:

```
my $nodetool_path = '/usr/bin/nodetool';
```

Once you've done that, execute `cassandra.pl` and you should see output similar to:

```
CASSANDRA OK - | heap_mem=8.01
```

Great, the plugin works. As explained earlier, the plugin has default thresholds for the heap memory usage. If you wanted to try other values, the following arguments can be used:

How to Monitor Apache Cassandra Databases in Nagios XI

```
./cassandra.pl --heap_w 5 --heap_c 95
```

In this example it outputs the following:

```
CASSANDRA WARNING - WARNING: 8% heap used; | heap_mem=8.05
```

The warning threshold I used on the example was not at all realistic, it was just used to demonstrate how the plugin thresholds can be defined

Configure NRPE

For Nagios XI to execute this plugin, you need to define a command for this plugin in the *nrpe.cfg* on the Cassandra server. Edit the */usr/local/nagios/etc/nrpe.cfg* file by executing the following command:

```
vi /usr/local/nagios/etc/nrpe.cfg
```

Add the following line to the end of the file:

```
command[cassandra]=/usr/local/nagios/libexec/cassandra.pl $ARG1$
```

After saving these changes, restart the *xinetd* service on the Cassandra Server (or the *nrpe* service if you compiled from source) by running the following command.

```
service xinetd restart
```

Now to test the check from the XI server. Establish a terminal session to your Nagios XI server and execute the following command, making sure to replace *<cassandra_server_ip>* with the IP address of your Cassandra server:

```
/usr/local/nagios/libexec/check_nrpe -H -c cassandra
```

You should see output similar to:

```
CASSANDRA OK - | heap_mem=7.21
```

If you receive that output, then everything is working. If you wanted to pass your own thresholds then the command to execute would be as follows (replace the IP after *-H* with your Cassandra IP) :

```
/usr/local/nagios/libexec/check_nrpe -H 10.25.7.31 -c cassandra -a '--heap_w 5 --heap_c 95'
```


How to Monitor Apache Cassandra Databases in Nagios XI

Now that NRPE has been configured correctly on your Cassandra server the next step is to create the monitoring configuration in Nagios XI.

Create Nagios Monitoring Objects

In this example you will use the NRPE Configuration Wizard which will create the host and service objects.

Navigate via the top menu bar to **Configure > Run a configuring wizard** and select the **NRPE** wizard. In the following screenshot you can see how the search field allows you to quickly find a wizard.



On **Step 1** you will be asked to supply the **IP Address** of the Cassandra server. You will also have to select the **Operating System**; in this case it is CentOS.



How to Monitor Apache Cassandra Databases in Nagios XI

Click **Next** to progress to step 2.

On **Step 2** you will configure all the options for monitoring.

To start off with, make sure a valid **Host Name** has been entered.

The **NRPE Agent** section can be ignored because you have already installed it.

The NRPE wizard allows you to specify which NRPE commands should be executed and monitored and what display name (service description) should be associated with each command.

In the screenshot to the right, you can see the command has been defined for the Cassandra check.

If you wanted to supply your own thresholds, you would type them in the Command Args field, for example:

```
--heap_w 5 --heap_c 95
```

Click **Next** and then complete the wizard by choosing the required options in Step 3 - Step 5.

To finish up, click on **Finish** in the final step of the wizard.

This will create new hosts and services and begin monitoring.

Once the wizard applies the configuration, click the View status details for link to see the new host and services that were created.

Display Name	Remote NRPE Command	Command Args
<input type="checkbox"/> Current Users	check_users	
<input type="checkbox"/> Current Load	check_load	
<input type="checkbox"/> Total Processes	check_total_procs	
<input checked="" type="checkbox"/> Cassandra Status	cassandra	

Host	Service	Status	Duration	Attempt	Last Check	Status Information
cassandra01	Cassandra Status	Ok	6m 30s	1/5	2017-02-14 15:13:11	CASSANDRA OK -


You are now monitoring your Cassandra server.

How to Monitor Apache Cassandra Databases in Nagios XI

Advanced Nagios Monitoring Configuration

Apache Cassandra is a distributed database, it's likely that you are going to have more than just one Cassandra server that you want to monitor. Instead of repeating those steps for each Cassandra server, you can use a Nagios advanced configuration technique by assigning a service to a host group (instead of to a specific host). By using this technique, all the hosts that are in this host group will receive the same services ... but there is only one service definition which in turn reduces your configuration complexity / overhead.

In this example I will add another two Cassandra servers using this method, but before we add the servers, I'll create the host group first. Navigate via the top menu bar to **Configure > Core Config Manager and then Monitoring > Host Groups**.



The screenshot shows the Nagios XI Core Config Manager interface. The top navigation bar includes Home, Views, Dashboards, Reports, Configure, Tools, Help, and Admin. The left sidebar has a 'Quick Tools' section with 'Core Config Manager' selected, and a 'Monitoring' section with 'Host Groups' selected. The main content area is titled 'Host Groups' and displays a table with two entries: 'linux-servers' (Active: Yes) and 'windows-servers' (Active: No). A '+ Add New' button is highlighted in blue. Below the table are buttons for '+ Add New', 'Apply Configuration', and a 'Go' button. A search bar is located in the top right corner.

<input type="checkbox"/>	Host Group Name	Alias	Active	Actions	ID
<input type="checkbox"/>	linux-servers	Linux Servers	Yes	    	1
<input type="checkbox"/>	windows-servers		No	    	2

Click the **+Add New** button.

A **Host Group Name and Description** is required.

Don't add any members to the group, this will be done via the host object.

Click **Save** to create the host group.

How to Monitor Apache Cassandra Databases in Nagios XI

Host Group Management

Host Group Name *

Description *

Notes

Notes URL

Action URL


Active ⓘ

Assign Memberships

0

0

The next step is to add the existing host as a member of the new group. Navigate to **Monitoring > Hosts**.



The screenshot shows the Nagios XI interface. The top navigation bar includes Home, Views, Dashboards, Reports, Configure, Tools, Help, and Admin. The left sidebar shows the Core Config Manager (CCM) and Monitoring sections. The Monitoring section is expanded, and 'Hosts' is selected. The main content area displays a table of hosts with columns for Host Name, Alias, Active, Status, Actions, and ID. Two hosts are listed: 'cassandra01' and 'localhost'. The 'cassandra01' host is selected, and the 'Modify' icon (a wrench) is circled in the Actions column. Below the table, there are buttons for '+ Add New', 'Apply Configuration', and a 'With checked' dropdown menu. A search bar is located at the top right of the Hosts page.

<input type="checkbox"/>	Host Name	Alias	Active	Status	Actions	ID
<input type="checkbox"/>	cassandra01		Yes	Applied	   	2
<input type="checkbox"/>	localhost	localhost	Yes	Applied	   	1


Click the **Modify** icon for the existing host.

Click the **Manage Host Groups** button.


Add the **Cassandra Servers** host group to the Assigned list.

How to Monitor Apache Cassandra Databases in Nagios XI

Click **Close** and then **Save**.



The next step is to change the existing service to use the new host group. Navigate to **Monitoring > Services**.




Click the **Manage Hosts** button.

Remove the existing host **cassandra01** from the Assigned list.

Click **Close**.

How to Monitor Apache Cassandra Databases in Nagios XI




Click the **Manage Host Groups** button.


Add the **Cassandra Servers** host group to the **Assigned** list.

Click **Close**.

How to Monitor Apache Cassandra Databases in Nagios XI



Finally, change the **Config Name** to something generic, because this service is no longer "tied" to the cassandra01 server.




Click **Save** and **Apply Configuration**.

At this point, technically all that has been done is to change the service from being assigned to a host, it is now assigned to a host group. In the next step, you'll add the remaining hosts, and they will receive the new **Cassandra Status** service.


To add the remaining hosts, the **Bulk Host Cloning and Import** wizard will be used to clone the existing host.

How to Monitor Apache Cassandra Databases in Nagios XI

Navigate via the top menu bar to **Configure > Run a configuring wizard** and select the **Bulk Host Cloning** and Import wizard. In the following screenshot you can see how the search field allows you to quickly find a wizard.



On **Step 1** you are required to select the host that you wish to use as the template that you will clone. The screenshot on the following page shows the host **cassandra01** has been selected. Click **Next** to continue.



In **Step 2**, the host you selected to use as the template is shown at the top. All the available services from the template host are listed under the **Select Template Services** section. In this example the only service listed is **Cassandra Status** and you can see that it says "Inherited - Can not be cloned using the wizard". This is exactly what we want, the new hosts will inherit this service when the wizard is completed.

How to Monitor Apache Cassandra Databases in Nagios XI

Configuration Wizard: Bulk Host Cloning and Import - Step 2

Host Template

cassandra01

Select Service Templates

Specify the services from the template host that should be cloned.

Check All / Uncheck All

Cassandra Status (Inherited - Can not be cloned using the wizard)

Import / Cloning Data

Enter addresses of new hosts that should be created by cloning the template host and services specified above.

Fields:

Field 1	Field 2	Field 3	Field 4	Field 5
Name	Address	IGNORE	IGNORE	IGNORE

Specify the type of data that is present in the fields of the data below.

Data:

```
cassandra02,10.20.1.22  
cassandra03,10.20.1.23
```

The addresses of new hosts that should be created by cloning the template host and services specified above. Multiple fields should be separated by a comma. One entry per line.

Options: Replace Parent Host and/or Hostgroup with the above selected (if any) instead of adding the given Parent and/or Hostgroup to the new host.

[< Back](#) [Next >](#)

Under the **Import / Cloning Data** section, the drop-down lists are the Nagios XI host object directives. These need to be mapped to each field of the CSV data that is provided in the **Data** text area.

The data provided is the remaining Cassandra hosts I am adding.

Looking at the screenshot to the right you can see:

Field 1 = Address

Field 2 = Name

Click **Next** to continue.

The remaining wizard steps have no settings, any options that are normally available in for these steps in Configuration Wizards will be inherited from the template host you selected. You can click **Finish** on any of the steps or click Next on each step and click **Apply** on the final step.

How to Monitor Apache Cassandra Databases in Nagios XI

Wait for the configuration wizard to create the new monitoring configs. The following screenshot shows the newly monitored hosts and services based on the data provided on step 2 (as well as the original host).

Host	Service	Status	Duration	Attempt	Last Check	Status Information
cassandra01	Cassandra Status	Ok	1h 44m 54s	1/5	2017-02-14 16:48:11	CASSANDRA OK -
cassandra02	Cassandra Status	Ok	3m 19s	1/5	2017-02-14 16:49:46	CASSANDRA OK -
cassandra03	Cassandra Status	Critical	3m 15s	4/5	2017-02-14 16:52:43	CASSANDRA CRITICAL - WARNING: Cassandra node is DOWN

You can see that one of the Cassandra nodes is down, the plugin is doing its job!

From the steps you were just shown, you can see how services can be applied to multiple hosts using host groups. This can be a time saver when creating monitoring configurations for identical type devices (like nodes in a cluster).

Finishing Up

This completes the documentation on monitoring Apache Cassandra databases in Nagios XI. If you have additional questions or other support-related questions, please visit us at our Nagios Support Forum, Nagios Knowledge Base, or Nagios Library:

[Visit Nagios Support Forum](#)

[Visit Nagios Knowledge Base](#)

[Visit Nagios Library](#)